



Fiber Optic Duplex Adapter, Multimode LC/UPC, OM3/OM4, aqua, flangeless

## Product Classification

Regional Availability	Asia   EMEA   Latin America   North America
Product Type	Fiber adapter

## General Specifications

Body Style	Duplex
Color	Aqua
Interface	LC/UPC
Mounting	No flange
Shuttered	No
Total Ports, quantity	2
Transmission Standards	IEC 60754-1   IEC 61300-3-42

## Dimensions

Width	15.4 mm   0.606 in
Length	29.2 mm   1.15 in

## Material Specifications

Alignment Sleeve Material	Zirconia
---------------------------	----------

## Optical Specifications

Fiber Mode	Multimode
Insertion Loss, maximum	0.2 dB

## Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Flammability Rating	UL 94 V-0

# EH1458-002

---

## Packaging and Weights

<b>Included</b>	Dust caps
<b>Packaging Type</b>	Bag

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

