# F1A-HFHR-16N-P



FSJ1-50A SureFlex® Jumper with interface types 4.3-10 Female and 4.3-10 Male Right angle, 16 inches

WARNING: DO NOT MATE WITH 4.1-9.5 DIN

#### **Product Classification**

**Product Type** SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

**Product Series** FSJ1-50A

General Specifications

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A4.3-10 FemaleInterface, Connector B4.3-10 Male

Specification Sheet Revision Level A

Dimensions

**Length** 0.406 m | 1.332 ft

Nominal Size 1/4 in

**Electrical Specifications** 

**3rd Order IMD** -107 dBm

**3rd Order IMD Test Method** Two +43 dBm carriers

#### VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698-960 MHz	1.152	23.02
1700-2200 MHz	1.152	23.02
2200-2700 MHz	1.152	23.02

## Jumper Assembly Sample Label





### **Environmental Specifications**

**Immersion Test Method** 

Meets IEC 60529:2001, IP68 in mated condition

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

