## CLT5XM-3M-CO



MQ Multiport cluster 5 ports cable assembly with interface type MQ female to Nex10 male, size 1/4", length 3 meters

### **Product Classification**

**Product Type** Wireless transmission cable assembly

Product Series MQ

**Warranty** Two years

### General Specifications

Attachment, Connector A Factory attached

Attachment, Connector B Factory attached

Body Style, Connector A Straight
Body Style, Connector B Straight
Interface, Connector A MQ Female
Interface, Connector B NEX10 Male

Specification Sheet Revision Level A

#### **Dimensions**

**Length** 3 m | 9.843 ft

Nominal Size 1/4 in

## Port Configuration

Pin Assignment	Label	
1	MQ5-1 (R+)	
2	MQ5-2 (CR+)	
3	MQ5-3(CL+)	
4	MQ5-4(L+)	
5	MQ5-5 (CAL)	

VSWR/Return Loss



# CLT5XM-3M-CO

Frequency Band	VSWR	Return Loss (dB)	Insertion Loss, typical (dB)
0-2700 MHz	1.151	23.1	1.3
2700-4200 MHz	1.201	20.8	1.6
4200-6000 MHz	1.352	16.5	2.1

### Mechanical Specifications

Minimum Bend Radius, multiple Bends25.4 mm | 1 inMinimum Bend Radius, single Bend25.4 mm | 1 in

## **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$ 

**Immersion Test Method** IEC 60529, IP67

### Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



### \* Footnotes

Warranty For more information, please consult our Product Warranty guidelines

