L5CLAMP-CNL-1B



KwikClamp™ Hanger for 7/8 in coaxial cable, single stack, C-Channel compatible; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box
General Specifications	
Cables per Hanger	1
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	Channel section 40 x 22 x 1.5 mm
Dimensions	
Maximum Stack Height	1
Height	121 mm 4.764 in
Width	45 mm 1.772 in
Length	32 mm 1.26 in
Compatible Diameter, maximum	28 mm 1.102 in
Compatible Diameter, minimum	26 mm 1.024 in
Nominal Size	7/8 in
Hanger Spacing, maximum	1.83 m 6.004 ft
Electrical Specifications	
Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB
Material Specifications	

Material Specifications

Material Type

Engineered plastic | Stainless steel

Page 1 of 2



L5CLAMP-CNL-1B

Mechanical Specifications

Vibration Survival	≥4 hours at resonant frequency	
Environmental Specifications		
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)	

≥500 hours in salt spray chamber
Five times cable weight
≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	36 cm 14.173 in
Width, packed	21 cm 8.268 in
Length, packed	22 cm 8.661 in
Included	Hardware
Packaging quantity	100
Weight, gross	10 kg 22.046 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power



an Amphenol company

Page 2 of 2

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 19, 2025