

#### Single Support Arm, 24 in, includes pipe

#### **Product Classification**

**Product Type** Support arms for ring mount

#### General Specifications

**Mounting** Ring mount

Pipe, quantity 1

#### **Dimensions**

 Height
 457.2 mm | 18 in

 Width
 254 mm | 10 in

 Length
 609.6 mm | 24 in

 Pipe Length
 457.2 mm | 18 in

 Pipe Outer Diameter
 114.3 mm | 4.5 in

 Stand-off Distance
 609.6 mm | 24 in

### Material Specifications

Material Type Hot dip galvanized steel

#### Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC

**Wind Rating Criteria** Four 72 in x 8 in panel antennas per sector

Wind Rating Test Method TIA/EIA-222-G

#### Packaging and Weights

Included Hardware | Stand-off arms

Packaging quantity 1

**Weight, net** 28.1 kg | 61.95 lb



# MT-197-24

## Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

\* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

