


R8CLAMP-CNL-2B



KwikClamp™ Hanger for RG8 cable, double stack, C-Channel compatible; includes hardware

Product Classification

| | |
|---------------|---|
| Product Type | Hanger kit |
| Product Brand | KwikClamp™ |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box |

General Specifications

| | |
|-------------------|----------------------------------|
| Cables per Hanger | 1 |
| Color | Black |
| Hanger Type | KwikClamp™ hanger |
| Mounting | Channel section 40 x 22 x 1.5 mm |

Dimensions

| | |
|------------------------------|-------------------|
| Maximum Stack Height | 2 |
| Height | 138 mm 5.433 in |
| Width | 32 mm 1.26 in |
| Length | 42 mm 1.654 in |
| Compatible Diameter, maximum | 11 mm 0.433 in |
| Compatible Diameter, minimum | 10 mm 0.394 in |
| Nominal Size | 3/8 in |
| Hanger Spacing, maximum | 1.83 m 6.004 ft |

Electrical Specifications

| | |
|-----------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |

Material Specifications

| | |
|---------------|--------------------------------------|
| Material Type | Engineered plastic Stainless steel |
|---------------|--------------------------------------|

R8CLAMP-CNLCN-2B

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Five times cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed 27 cm | 10.63 in

Width, packed 21 cm | 8.268 in

Length, packed 11 cm | 4.331 in

Included Hardware

Packaging quantity 100

Weight, gross 4.89 kg | 10.781 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power