# R8CLAMP-CNL-3B



KwikClamp™ Hanger for RG8 cable, triple stack, C-Channel compatible; includes hardware

#### **Product Classification**

Product TypeHanger kitProduct BrandKwikClamp™

Ordering Note ANDREW® standard product in Europe, the Middle East, and

Africa | Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger 1

**Color** Black

**Hanger Type** KwikClamp™ hanger

Mounting Channel section 40 x 22 x 1.5 mm

**Dimensions** 

Maximum Stack Height 3

 Height
 165 mm | 6.496 in

 Width
 32 mm | 1.26 in

 Length
 42 mm | 1.654 in

 Compatible Diameter, maximum
 11 mm | 0.433 in

 Compatible Diameter, minimum
 10 mm | 0.394 in

Nominal Size 3/8 in

Hanger Spacing, maximum 1.83 m | 6.004 ft

**Electrical Specifications** 

 Return Loss Effect, maximum
 0.1 dB

 DTF Effect, maximum
 0.1 dB

Material Specifications

Material Type Engineered plastic | Stainless steel



# R8CLAMP-CNL-3B

### Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## **Environmental Specifications**

Operating Temperature  $-40 \,^{\circ}\text{C}$  to  $+70 \,^{\circ}\text{C}$  ( $-40 \,^{\circ}\text{F}$  to  $+158 \,^{\circ}\text{F}$ )

**Corrosion Resistance, minimum with no degredation** ≥500 hours in salt spray chamber

Environmental Strength Capability Five times cable weight

**UV Resistance, minimum with no degradation** ≥100 hours exposure in accelerated UV life chamber

## Packaging and Weights

 Height, packed
 27 cm | 10.63 in

 Width, packed
 21 cm | 8.268 in

 Length, packed
 11 cm | 4.331 in

**Included** Hardware

Packaging quantity 100

**Weight, gross** 6.74 kg | 14.859 lb

### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power