

LS2-XMDM-2M-P



LSF2-50 SureFlex® Jumper with interface types NEX10 Male and 7/16DIN Male, 2m

Product Classification

Product Type	SureFlex® Premium, static PIM
Product Brand	HELIAX® SureFlex®
Product Series	LSF2-50

General Specifications

Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	NEX10 Male
Interface, Connector B	7-16 DIN Male
Specification Sheet Revision Level	A

Dimensions

Length	2 m 6.562 ft
Nominal Size	3/8 in

Electrical Specifications

3rd Order IMD	-112 dBm
3rd Order IMD Test Method	Two +43 dBm carriers

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.065	30
1700–2200 MHz	1.083	28
2500–2700 MHz	1.106	26
3400–3800 MHz	1.222	20

Jumper Assembly Sample Label



Meets IEC 60529:2001, IP68 in mated condition

Regulatory Compliance/Certifications

Classification

Compliant as per SVHC revision on www.andrew.com/ProductCompliance

Included Products

LS2DM-S2	–	7/16 Male for 3/8 in LSF2-50 cable, factory attached
LS2XM-P	–	NEX10 Male for 3/8 in LSF2-50 cable, factory attached
LSF2-50	–	LSF2-50, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 3/8 in, black PE jacket (Not for Individual Sale - Jumpers only)