

# L4-DRDR-2M-D



D-CLASS LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male Right Angle and 7-16 DIN Male Right Angle , 2 m

## Product Classification

|                |                                |
|----------------|--------------------------------|
| Product Type   | SureFlex® D-CLASS, dynamic PIM |
| Product Brand  | HELIAX®   SureFlex®            |
| Product Series | LDF4-50A                       |

## General Specifications

|                                    |               |
|------------------------------------|---------------|
| Body Style, Connector A            | Right angle   |
| Body Style, Connector B            | Right angle   |
| Interface, Connector A             | 7-16 DIN Male |
| Interface, Connector B             | 7-16 DIN Male |
| Specification Sheet Revision Level | A             |

## Dimensions

|              |                |
|--------------|----------------|
| Length       | 2 m   6.562 ft |
| Nominal Size | 1/2 in         |

## Logo Image

# L4-DRDR-2M-D



## Electrical Specifications

|                                   |                                    |
|-----------------------------------|------------------------------------|
| 3rd Order IMD Dynamic             | -116 dBm                           |
| 3rd Order IMD Dynamic Test Method | Two +43 dBm carriers per IEC 62037 |
| DTF, Connector A                  | -32 dB                             |
| DTF, Connector B                  | -32 dB                             |

## VSWR/Return Loss

| Frequency Band | VSWR  | Return Loss (dB) | VSWR, typical | Return Loss, typical (dB) |
|----------------|-------|------------------|---------------|---------------------------|
| 698–960 MHz    | 1.083 | 28               |               |                           |
| 1700–2200 MHz  | 1.083 | 28               |               |                           |
| 2200–2700 MHz  | 1.135 | 24               |               |                           |
| 3400–3800 MHz  |       |                  | 1.222         | 20                        |

## Jumper Assembly Sample Label

# L4-DRDR-2M-D



## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Included Products

- LDF4-50A – LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket Halogen free jacketing non-fire-retardant (General propose cable for outdoor use only)