F4P43-HM-5M

FSJ4-50B SureFlex® Jumper with interface types 4.3-10 Male and open end, 5m

Product Classification

Product Type	SureFlex® Premium, static PIM	
Product Brand	HELIAX® SureFlex®	
Product Series	FSJ4-50B	
General Specifications		
Body Style, Connector A	Straight	
Interface, Connector A	4.3-10 Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	5 m 16.404 ft	
Nominal Size	1/2 in	
Electrical Specifications		
DTF, Connector A	-34 dB	
\/S\A/D/Doturn Loss		

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
710-806 MHz	1.201	20.8
806–960 MHz	1.151	23.1
1420-1530 MHz	1.151	23.1
1700–2180 MHz	1.151	23.1
2535–2655 MHz	1.201	20.8

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F4P43-HM-5M



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2