


VV-65A-R1B-KTE



Kit with one 4-port sector antenna model VV-65A-R1 (4x 1695–2690 MHz, 65° HPBW, 1x RET#The two high band arrays utilize a common tilt.)

- 1 x ATCB-B01-003 Cable 3m, RET to RRU
- The RET interface comprises one pair of AISG input/output ports

General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	PVC, UV resistant
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male
Input Voltage	10–30 Vdc
Internal RET	High band (1)
Power Consumption, idle state, maximum	2 W
Power Consumption, normal conditions, maximum	10 W
Protocol	3GPP/AISG 2.0

Dimensions

VV-65A-R1B-KTE

Width	307 mm 12.087 in
Depth	118 mm 4.646 in
Length	1390 mm 54.724 in
Net Weight, without mounting kit	10.8 kg 23.81 lb

Array Layout

Array ID	Frequency (MHz)	RF Connector	HPBW	RET (SRET)	AISG No.	AISG RET UID
Y1	1695-2690	1 - 2	65°	1	AISG1	CPxxxxxxxxxxxxxY1
Y2	1695-2690	3 - 4	65°			

(Sizes of colored boxes are not true depictions of array sizes)

Y1

Y2

Port Configuration



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2690 MHz
Polarization	±45°
Total Input Power, maximum	400 W @ 50 °C

VV-65A-R1B-KTE

Electrical Specifications

Frequency Band, MHz	1695–1880	1850–1990	1920–2200	2300–2500	2490–2690
Gain, dBi	17.5	17.7	18.2	18.5	18.6
Beamwidth, Horizontal, degrees	66	65	66	63	62
Beamwidth, Vertical, degrees	6.9	6.5	6.1	5.4	5.2
Beam Tilt, degrees	0–12	0–12	0–12	0–12	0–12
USLS (First Lobe), dB	17	18	18	21	21
Front-to-Back Ratio at 180°, dB	30	31	32	29	30
Isolation, Cross Polarization, dB	30	30	30	30	30
Isolation, Inter-band, dB	28	28	28	28	28
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153
Input Power per Port at 50°C, maximum, watts	300	300	300	300	250

Mechanical Specifications

Wind Loading @ Velocity, frontal	494.0 N @ 150 km/h (111.1 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	102.0 N @ 150 km/h (22.9 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	598.0 N @ 150 km/h (134.4 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	404 mm 15.906 in
Depth, packed	278 mm 10.945 in
Length, packed	1527 mm 60.118 in
Weight, gross	19.8 kg 43.651 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant

VV-65A-R1B-KTE

UK-ROHS

Compliant



Included Products

- | | | |
|--------------|---|---|
| 600899A-2 | - | Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set. |
| ATCB-B01-003 | - | AISG RET Control Cable, 3 m |

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
-------------------------	---