CMAX-LHM2-30-153



Low PIM Directional High Capacity Venue 2x2 MIMO Antenna 4G/5G/C-Band, 617–960 MHz, 1695–2700 MHz and 3300-4200MHz, 4.3-10

Product Classification

Product Type Over-the-head stadium antenna

General Specifications

Application Indoor/Outdoor

Antenna TypeDirectionalAntenna Array CharacteristicMIMO 2x2

 $\textbf{Polarization} \hspace{2cm} \pm 45^{\circ}$

Color Light Gray (RAL 7035)

Number of Ports 2

RF Connector InterfacePVC, UV resistant
4.3-10 Female

Dimensions

 Height
 140 mm | 5.512 in

 Width
 417 mm | 16.417 in

 Length
 700 mm | 27.559 in

Electrical Specifications

Impedance50 ohmLightning Protectiondc Ground

Operating Frequency Band 1695 – 2700 MHz | 3300 – 4200 MHz | 617 – 698 MHz | 698 – 960 MHz

Electrical Specifications

Frequency Band, MHz	617-698	698-960	1695-2700	3300-4200
Gain, dBi	10.1	11.1	10.7	10.1
Beamwidth, Horizontal, degrees	38	29	31	30
Beamwidth, Vertical, degrees	70	70	73	71

ANDREW® an Amphenol company

Page 1 of 3

CMAX-LHM2-30-153

Horizontal Sidelobe, dB	14	14	15	15
Front-to-Back Total Power at 180° ± 30°, dB	20	20	20	15
CPR at Boresight, dB	16	18	16	18
Isolation, Cross Polarization, dB	20	20	20	20
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153
Input Power per Port, maximum, watts	200	200	200	200

VSWR/Return Loss

Frequency Band	VSWR, Maximum	Return Loss, Maximum (dB)	VSWR, Mean	Return Loss, Mean (dB)
617-800 MHz	1.725	11.5	1.499	14
800-960 MHz	1.725	11.5	1.499	14
1695-2200 MHz	1.725	11.5	1.499	14
2200-2700 MHz	1.725	11.5	1.499	14
3300-4200 MHz	1.703	11.7	1.499	14

Mechanical Specifications

Wind Loading @ Velocity, maximum 947.0 N @ 241 km/h (212.9 lbf @ 150 mph)

Wind Speed, maximum 241.4 km/h (150 mph)

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +60 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +140 \,^{\circ}\text{F})$

Relative Humidity Up to 100%

Ingress Protection Test Method IEC 60529:2001, IP65

Vibration Test Method ASTM D4169 | IEC 60068-2-6

Packaging and Weights

 Height, packed
 235 mm | 9.252 in

 Width, packed
 480 mm | 18.898 in

 Length, packed
 940 mm | 37.008 in

 Included
 Mounting bracket

 Net Weight, with mounting kit
 10.4 kg | 22.928 lb

Packaging quantity 1

Weight, gross 13.8 kg | 30.424 lb



CMAX-LHM2-30-I53

Weight, net

7.6 kg | 16.755 lb

