

SRC3-U5A1B1BC000



NOVUX™ Specialty Range Closure 100, splice only, no adapters, no splitters, 12 splices, SMOUV® 45mm splice protectors, black, 2x NVX-CR-MC-RD-NN cable retention

- Modern drop solution offering providers the agility and flexibility to use it in last-mile fiber network applications, both above and below ground
- Protected from harsh conditions by CommScope’s Octopus gel sealing technology
- Agnostic to connectivity technologies: splice, connector, field-installable connector for agility and flexibility
- Identification plate for either QR code or customer logo
- QR code and CommScope cTrak® app for one-click access to all product information

Product Classification

Regional Availability	Asia EMEA Latin America North America
Regional Availability Note	Contact your local CommScope representative for specific availability
Product Type	Single-ended, rectangular fiber closure
Product Brand	NOVUX™
Product Series	SRC100

General Specifications

Cable Capacity, Drop	4 Flat 8.0 x 4.5 mm (0.30 x 0.17 in) 4 Round 1.2–8.0 mm (0.05–0.31 in)
Cable Ports Quantity, total	4 multi-out ports (8 cables)
Cable Sealing Type	Compressed gel
Cable Termination Attachments, quantity	2
Closure Sealing Type	Hinged with latch
Closure Style	Single-ended
Color	Black
Mounting	Handhole Pedestal Wall/Pole Mount, mounting kit included
Network Area Type	Drop
Port Type	No adapter No adapter
Port, quantity	0
Splice Tray Included, quantity	1
Splice Tray Type Included	12-way, heat shrink
Splicing Capacity, maximum	12

SRC3-U5A1B1BC000

Splicing Capacity, Single Fusion, maximum	12
Splicing Type, Supported	Single fusion
Splitter Type	No splitter
Splitter, quantity	0
Dimensions	
Height	267 mm 10.512 in
Width	117 mm 4.606 in
Depth	49 mm 1.929 in
Cable Entry Drop Port Diameter	8 mm (0.31 in) mm

Ordering Tree

SRC

-U

000

Size and color

3

100 Black

4

100 Gray

Sealing

U

Underground, IP68

Connector type*

1

SC/UPC

2

LC/UPC

3

SC/APC

4

LC/APC

5

Splice only

*All connector types are grade B

Number of adapters

A

None

K

1

B

2

Cable retention

*

See complete details at the bottom of the page.

Splice protector type

A

ANT/SMOUV 30

B

SMOUV 45

F

Ribbon 12

Splitters

1

None

2

1:2

3

1:4

Number of splices

B

12

C

24

D

48

Number of pigtails

1

None

A

1

2

2

B

3

3

4

2 cable attachments are supplied.

Cable retention*

A

None

B

NVX-CR-MC-FT-NN

C

NVX-CR-MC-RD-NN

D

NVX-CR-SA-SM-NN

E

NVX-CR-TI-SM-NN

F

NVX-CR-DU-FL-NN

G

4xNVX-CR-MC-FT-NN

H

4xNVX-CR-MC-RD-NN

I

4xNVX-CR-SA-SM-NN

J

4xNVX-CR-TI-SM-NN

K


4xNVX-CR-DU-FL-NN

L

2xNVX-CR-MC-FT-NN and 2xNVX-CR-MC-RD-NN

Cable Termination Unit (CTU) options

B




NVX-CR-MC-FT-NN

• Flat cable

• Metal clip

• Range 3 x 5 to 4 x 8 mm

C




NVX-CR-MC-RD-NN

• Round cable

• Metal clip

• Range 4 to 6.2 mm

D



NVX-CR-SA-SM-NN

• Round cable


• Dia up to 8 mm

• Strength member

• Aramide yarns

• Single layer

E



NVX-CR-TI-SM-NN


• Round cable

• Dia up to 8 mm

• Aramide yarns

• Single layer

F



NVX-CR-DU-FL-NN

• Round cable

• Dia up to 6.2 mm

• Aramide yarns

• Dual layer

• Compact length

Page 2 of 4

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see <https://www.commscope.com/trademarks>. All product names, trademarks and registered trademarks are property of their respective owners. Revised: May 17, 2024

COMMScope®

SRC3-U5A1B1BC000

Material Specifications

Material Type Impact-resistant polymer

Optical Specifications

Fiber Type G.652.D | G.657.A1 | G.657.A2 | G.657.B3

Environmental Specifications

Operating Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Environmental Space Above ground | Below ground | Direct burial

Qualification Standards IEC 60529, IP68 + 2 m waterhead | IEC 61753-1, category G

UV Resistance UV stabilized

Water Resistance Flash test valve at 2 psi (20 kPa)

Packaging and Weights

Packaging quantity 10

Packaging Type Box | Carton

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

Included Products

NVX-CR-MC-RD-NN	–	NOVUX™ Cable Termination Unit (CTU) for round cables with 4 to 6,2 mm diameter, metal clip
-----------------	---	--

NVX-CR-MC-RD-NN



NOVUX™ Cable Termination Unit (CTU) for round cables with 4 to 6,2 mm diameter, metal clip

Product Classification

Regional Availability	Asia EMEA Latin America North America
Product Type	Cable termination kit
Product Brand	NOVUX™
Product Series	CSC

General Specifications

Application	For use with CSC Fiber closures
Color	Black

Packaging and Weights

Packaging quantity	20
Packaging Type	Bag Box

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

