CLT4NM-6M-CO



MQ Multiport cluster 4 ports cable assembly with interface type MQ female to N male, size 1/4", length 6 meters

Product Classification

Product Type Wireless transmission cable assembly

Product Series MQ

Warranty Two years

General Specifications

Attachment, Connector A Factory attached

Attachment, Connector B Factory attached

Body Style, Connector A

Body Style, Connector B

Interface, Connector A

MQ Female

Interface, Connector B

N Male

Specification Sheet Revision Level

A

Dimensions

Length 6 m | 19.685 ft

Nominal Size 1/4 in

Port Configuration

| Pin Assignment | Label |
|----------------|-------------|
| 1 | MQ4-1 (R-) |
| 2 | MQ4-2(CR-) |
| 3 | MQ4-3 (CL-) |
| 4 | MQ4-4 (L-) |

VSWR/Return Loss



CLT4NM-6M-CO

| Frequency Band | VSWR | Return Loss (dB) | Insertion Loss, typical (dB) |
|----------------|-------|------------------|------------------------------|
| 0-2700 MHz | 1.151 | 23.1 | 2.4 |
| 2700-4200 MHz | 1.201 | 20.8 | 3 |
| 4200-6000 MHz | 1.352 | 16.5 | 4 |

Mechanical Specifications

Minimum Bend Radius, multiple Bends25.4 mm | 1 inMinimum Bend Radius, single Bend25.4 mm | 1 in

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$

Immersion Test Method IEC 60529, IP67

* Footnotes

Warranty For more information, please consult our Product Warranty guidelines