CLT5NM-4M-CO



MQ Multiport cluster 5 ports cable assembly with interface type MQ female to N male, size 1/4", length 4 meters

Product Classification

Product TypeWireless transmission cable assembly

Product Series MQ

Warranty Two years

General Specifications

Attachment, Connector A Factory attached

Attachment, Connector B Factory attached

Body Style, Connector A Straight

Body Style, Connector B Straight

Interface, Connector A MQ Female

Interface, Connector B N Male

Specification Sheet Revision Level A

Dimensions

Length 4 m | 13.123 ft

Nominal Size 1/4 in

Port Configuration

Pin Assignment	Label	
1	MQ5-1 (R+)	
2	MQ5-2(CR+)	
3	MQ5-3 (CL+)	
4	MQ5-4(L+)	
5	MQ5-5 (CAL)	

VSWR/Return Loss



CLT5NM-4M-CO

Frequency Band	VSWR	Return Loss (dB)	Insertion Loss, typical (dB)
0-2700 MHz	1.151	23.1	1.65
2700-4200 MHz	1.201	20.8	2.05
4200-6000 MHz	1.352	16.5	2.65

Mechanical Specifications

Minimum Bend Radius, multiple Bends25.4 mm | 1 inMinimum Bend Radius, single Bend25.4 mm | 1 in

Environmental Specifications

Operating Temperature $-40 \, ^{\circ}\text{C} \text{ to } +85 \, ^{\circ}\text{C} \, (-40 \, ^{\circ}\text{F to } +185 \, ^{\circ}\text{F})$

Immersion Test Method IEC 60529, IP67

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



* Footnotes

Warranty For more information, please consult our Product Warranty guidelines

