

# L4A-HMDF-P-SGW

Base Product



LDF4-50A SureFlex® Jumper with interface type 4.3-10 Male and 7-16 female, with HELIAX® SureGuard weatherproofing

## Product Classification

|                |                               |
|----------------|-------------------------------|
| Product Type   | SureFlex® Premium, static PIM |
| Product Brand  | HELIAX®   SureFlex®           |
| Product Series | LDF4-50A                      |

## General Specifications

|                                    |  |
|------------------------------------|--|
| Attachment, Connector A            | Factory attached   |
| Attachment, Connector B            | Factory attached   |
| Body Style, Connector A            | Straight   |
| Body Style, Connector B            | Straight   |
| Interface, Connector A             | 4.3-10 Male  |
| Interface, Connector B             | 7-16 DIN Female  |
| Specification Sheet Revision Level | A  |
| Variable Length                    | For custom lengths, contact your local ANDREW representative |

## Dimensions

|                                  |         |
|----------------------------------|---------|
| Cable Assembly Length Range (ft) | 5 – 140 |
| Nominal Size                     | 1/2 in  |

## Electrical Specifications

|                                  |                      |
|----------------------------------|----------------------|
| 3rd Order IMD Static             | -119 dBm             |
| 3rd Order IMD Static Test Method | Two +43 dBm carriers |
| DTF, Connector A                 | -32 dB               |
| DTF, Connector B                 | -32 dB               |

# L4A-HMDF-P-SGW

## Jumper Assembly Sample Label



## Environmental Specifications

|                               |   |
|-------------------------------|---|
| <b>Immersion Test Method</b>  | Meets IEC 60529:2001, IP68 in mated condition |
| <b>Weatherproofing Method</b> | HELIAX® SureGuard weatherproofing boot        |