


F4A-HFHR-P

Base Product



HELIAX® 1/2" SureFlex® Jumper with interface types 4.3-10 Female and 4.3-10 Right Male

Product Classification

| | |
|----------------|-------------------------------|
| Product Type | SureFlex® Premium, static PIM |
| Product Brand | HELIAX® SureFlex® |
| Product Series | RSJ4-50 |

General Specifications

| | |
|------------------------------------|--|
| Attachment, Connector A | Factory attached |
| Attachment, Connector B | Factory attached |
| Body Style, Connector A | Straight |
| Body Style, Connector B | Right angle |
| Specification Sheet Revision Level | A |
| Variable Length | For custom lengths, contact your local ANDREW representative |

Dimensions

| | |
|---------------------------------|--------|
| Cable Assembly Length Range (m) | 1 – 15 |
|---------------------------------|--------|

Electrical Specifications

| | |
|----------------------------------|------------------------------------|
| 3rd Order IMD Static | -112 dBm |
| 3rd Order IMD Static Test Method | Two +43 dBm carriers per IEC 62037 |
| DTF, Connector A | -34 dB |
| DTF, Connector B | -34 dB |

Jumper Assembly Sample Label

F4A-HFHR-P



Environmental Specifications

Immersion Test Method Meets IEC 60529:2001, IP68 in mated condition