

Monopole Co-location Dual Pipe Mount Base Kit, 12 in to 50 in OD, 5 ft 6 in face, pipe ordered separately

Product Classification

Product TypeCo-location dual pipe mount kit

General Specifications

Monopole, 304.8–1270 mm (12–50 in) OD

Pipe, quantity 0
Sectors, quantity 3

Dimensions

Height 254 mm | 10 in **Face Width** 2.012 m | 6.6 ft Width 1,676.4 mm | 66 in Length 355.6 mm | 14 in 1270 mm | 50 in Mounting Diameter, maximum Mounting Diameter, minimum 304.8 mm | 12 in **Pipe Outer Diameter** 88.9 mm | 3.5 in Stand-off Distance 355.6 mm | 14 in

Mounting Circumference, maximum 3,990.34 mm | 157.1 in

Mounting Circumference, minimum 1,196.34 mm | 47.1 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 100 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D

per FBC



Page 1 of 2

MC-HPM1250-B

Wind Rating Criteria Four 72 in x 12 in panel antennas per sector

Wind Rating Test Method TIA/EIA-222

Packaging and Weights

Included Dual pipe frames | Pipe mounts | Ring mount

Packaging quantity 1

Weight, net 242.309 kg | 534.2 lb

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

