## L4A-HPNMNM-15M

LDF4-5	OA SureFlex® Jumper with interface types N Male and N Male,
∎ <b>⊒⊐=========</b> 15m	

## Product Classification

Product Type	SureFlex® HP, HELIAX®	) performance
Product Brand	HELIAX®   SureFlex@	)
Product Series	LDF4-50A	
General Specifications		
Body Style, Connector A	Straight	
Body Style, Connector B	Straight	
Interface, Connector A	N Male	
Interface, Connector B	N Male	
Specification Sheet Revision Level	А	
Dimensions		
Length	15 m   49.213 ft	
Nominal Size	1/2 in	
Electrical Specifications		
3rd Order IMD Static Test Method	Two +43 dBm carriers	
3rd Order IMD, typical	-112 dBm	
DTF, Connector A	-34 dB	
DTF, Connector B	-34 dB	
VSWR/Return Loss		
Frequency Band	VSWR, typical	Return Los
680–960 MHz	1.101	26.4

 Frequency Band
 VSWR, typical
 Return Loss, typical (dB)

 680-960 MHz
 1.101
 26.4

 1700-2200 MHz
 1.101
 26.4

 2200-2700 MHz
 1.135
 24

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

## L4A-HPNMNM-15M

Jumper Assembly Sample Label



**Environmental Specifications** 

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2