F1A-XRHM-PB

Base Product

FSJ1-50A SureFlex® Jumper with Integrated Bird-proofing shell with 💻 interface types NEX10 Male Right Angle and 4.3-10 Male, variable length

Product Classification

Product Type		Wireless transmission cable assembly	
Product Series		FSJ1-50A	
General Specifications			
Body Style, Connector A		Right angle	
Body Style, Connector B		Straight	
Interface, Connector A		NEX10 Male	
Interface, Connector B		4.3-10 Male	
Specification Sheet Revision Level		A	
Variable Length		For custom lengths, contact your local ANDREW representative	
Dimensions			
Nominal Size		1/4 in	
Electrical Specifications			
3rd Order IMD		-107 dBm	
3rd Order IMD Test Method		Two +43 dBm carriers	
VSWR/Return Loss			
Frequency Band	VSWR	Return Loss (dB)	
698–960 MHz	1.152	23	

1700-2200 MHz	1.152	23
2200-2700 MHz	1.152	23

Jumper Assembly Sample Label

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

F1A-XRHM-PB



Environmental Specifications

Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition



an Amphenol company

©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 18, 2025

Page 2 of 2