CLT5DM-3M-CO



MQ Multiport cluster 5 ports cable assembly with interface type MQ female to 7/16DIN male, size 1/4", length 3 meters

Product Classification

Product Type	Wireless transmission cable assembly
Product Series	MQ
Warranty	Two years
General Specifications	
Attachment, Connector A	Factory attached
Attachment, Connector B	Factory attached
Body Style, Connector A	Straight
Body Style, Connector B	Straight
Interface, Connector A	MQ Female
Interface, Connector B	7-16 DIN Male
Specification Sheet Revision Level	А

Dimensions

Length	3 m 9.843 ft
Nominal Size	1/4 in

Port Configuration

Pin Assignment	Label
1	MQ5-1(R+)
2	MQ5-2(CR+)
3	MQ5-3(CL+)
4	MQ5-4(L+)
5	MQ5-5(CAL)

VSWR/Return Loss

Page 1 of 2



©2025 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners. Revised: March 20, 2025

CLT5DM-3M-CO

Frequency Band	VSWR	Return Loss (dB)	Insertion Loss, typical (dB)
0–2700 MHz	1.151	23.1	1.3
2700–4200 MHz	1.201	20.8	1.6
4200–6000 MHz	1.352	16.5	2.1
Mechanical Specifica	tions		
Minimum Bend Radius, multiple	Bends	25.4 mm 1 in	
Minimum Bend Radius, single Be	end	25.4 mm 1 in	
	·		

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Immersion Test Method	IEC 60529, IP67

* Footnotes

Warranty For more information, please consult our Product Warranty guidelines



