



ERA® O-RAN Digital Donor

- Single height ERA WCS card
- Use in WIN and CAN configurations
- ORAN 7.2a Split, version 6.0 compatible
- Compatible with Samsung vDU and uADPF
- 10 Gbps SFP+ interfaces
- 4G LTE and 5G NR FDD supported
- 5G NR TDD supported
- 2x2 MIMO support
- 320MHz Total BW
- All LTE/NR channel BW >= 5 MHz supported
- Supports all ERA RUs
- Supports C-band TDD, B13, Cell 850, AWS, and PCS FDD (other bands coming soon)

Product Classification

Product Type	Card
Product Brand	ERA®

General Specifications

Device Type	Card
General Alarm	Integrated into management system
Input Connector Interface	LC SFP+
Input Connector, quantity	2
Management Interface	Integrated into management system
Note	Detailed Product Specifications are available. Please contact your local ANDREW representative.
Required Subrack Version	WCS-2 SUBRACK (7635443-03) WCS-2 SUBRACK (A7635443-03) WCS-4 SUBRACK (7635442-03) WCS-4 SUBRACK (A7635442-03) WCS2 SUBRACK, INTEGRATED DC PSU (7844067-02) WCS2 SUBRACK, INTEGRATED DC PSU (A7844067-02) WCS4 SUBRACK, INTEGRATED DC PSU (7844068-02) WCS4 SUBRACK, INTEGRATED DC PSU (A7844068-02)

Dimensions

Height	20 mm 0.787 in
Width	145 mm 5.709 in
Depth	300 mm 11.811 in

Packaging and Weights

Height, packed	63 mm 2.48 in
Width, packed	210 mm 8.268 in
Depth, packed	362 mm 14.252 in
Weight, gross	1 kg 2.205 lb
Weight, net	0.6 kg 1.323 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

