



Propel Singlemode Splice Cassette, 12LC/APC with internal shutters, 250 μ m OS2 single fiber pigtails, pairs straight ULL

- Can be installed and removed from front or rear of panel
- This component requires 3 of the 12 lanes on the Propel Panel blade
- Compatible with either 250 μ m or 900 μ m incoming fiber

Product Classification

| | |
|-----------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Portfolio | CommScope® |
| Product Type | Fiber cassette with pigtails |
| Product Brand | Propel |
| Product Series | PPL |

General Specifications

| | |
|------------------------|------------------|
| Color, front | Green |
| Interface, front | LC/APC |
| Interface, rear | Stranded pigtail |
| Polarity | Pairs, straight |
| Shuttered | Yes |
| Total Fibers, quantity | 12 |

Dimensions

| | |
|--------|----------------------|
| Height | 67.31 mm 2.65 in |
| Width | 97.993 mm 3.858 in |

Optical Specifications

| | |
|-------------------------|------------|
| Fiber Mode | Singlemode |
| Fiber Type | G.657.A2 |
| Insertion Loss, maximum | 0.25 dB |

Environmental Specifications

| | |
|-------------------------|---------------------------|
| Qualification Standards | IEC 61753-1 TIA-568.3-D |
|-------------------------|---------------------------|

Safety StandardUL

Packaging and Weights

IncludedMass Fusion Splice Protection Sleeves

Packaging quantity1

Regulatory Compliance/Certifications

| Agency | Classification |
|------------|-----------------------------------|
| CHINA-ROHS | Below maximum concentration value |
| ROHS | Compliant |
| UK-ROHS | Compliant |

