PPLAGX8LCQPU

Propel ULL Multimode OM4 Cabled Module, 8x8 duplex LC Propel module on End A to 1x8f MPO /UPC non-pinned on End B, 64 fiber Plenum Trunk, Method A

- This component requires 16 lanes on the Propel Panel blade
- Ultra-low loss (ULL) with Method A polarity
- End A module can be installed from rear of panel
- Serialized QR code provides easy access to factory optical test results

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio SYSTIMAX®

Product Type Fiber cabled module

Product Brand Propel
Product Series PPL

Ordering Note For lengths greater than 999 ft (304 m), orders must be in meters | Maximum length is

400 meters

General Specifications

Configuration Type PROPEL Module to MPO Connector

Cable Color Aqua

Cable TypeTrunk Cable - Plenum

Interface, front LC/UPC

Interface Feature, front Duplex | Shuttered

Interface Color, front Aqua

Interface, rear MPO-08/UPC Female

Interface Feature, rear Key up/down | Unpinned

Module Size, end A8 fiberModule Size, end B8 fiberModule Quantity, end A8

Module Quantity, end B 8

Polarity Method A

Total Fibers, quantity 64

Total Ports, quantity, front 32



PPLAGX8LCQPU

Dimensions

 Height
 11 mm | 0.433 in


 Width
 98 mm | 3.858 in

 Depth
 170 mm | 6.693 in

Breakout Length, end B 12 in | 120 in | 33 in | 36 in | 48 in | 60 in | 72 in

Cable Assembly Length Range (m) 1-400 Cable Assembly Length Range (ft) 2-999

Ordering Tree



Optical Specifications

Fiber ModeMultimodeFiber TypeOM4Insertion Loss, maximum0.35 dB

Environmental Specifications

Qualification Standards IEC 61753-1 | TIA-568.3-D

Safety Standard c-UL-us

Packaging and Weights

Packaging quantity 1

COMMSCOPE®

PPLAGX8LCQPU

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



Included Products

760248183 – Fiber indoor cable, LazrSPEED® Plenum MPO Trunk, 64 fiber multi-unit with 8 fiber subunits, P-064-MP-5K-F08AQ/20T Multimode OM4, Gel-free, Feet jacket marking, Aqua jacket color