			4				3		
D	 1.0 GENERAL NOTES 1.1 ALL METRIC DIMENSIONS ARE IN BRACKETS [X. X] 1.2 FOR PATENT INFO: https://www.cs-pat.com 2.0 DESIGN NOTES 2.1 ANY HAZARDS OR OBSTRUCTIONS TO THE CLIMBING FACILITY AND SAFETY CLIMB MUST BE IDENTIFIED PRIOR TO INSTALLING THE APPURTENANCE. ADDITIONAL PRODUCTS MAY BE REQUIRED TO MAINTAIN THE INTEGRITY OF THE SAFETY CLIMB. DURING INSTALLATION, TEMPORARY AND/OR PERMANENT PRECAUTIONARY MEASURES SHOULD BE TAKEN TO PRESERVE THE CLIMBING FACILITY AND/OR SAFETY CLIMB. 3.0 MANUFACTURING/SPECIAL REQUIREMENTS 3.1 TIGHTEN ALL BOLTS SECURING FLAT PLATES BY THE TURN-OF-NUT METHOD. TIGHTEN ALL U-BOLTS 								
	4.0 TES 5.0 PAC 5.1 5.2	EACH LEG OF THE U-BC T KAGING PACKAGING SHALL MEE PRINTED DOCUMENT T(DLT. ET COMMSCOF D BE PLACED	ATTENTION TO LEAVE EQUAL E PE REQUIREMENTS PER DOCU NSIDE POLYBAG AND THEN IN D, BAGGED AND SHIPPED	MENT IS-PL-300	5			
				BOLT ATTACHES GRIP ANCHOR TO CABLE LADD	ER				
С									
В									
	◄ (19.64[498.9])								
	GRIP ANCHOR								
	COMP	ONENT PART NU	MBERS PR	OVIDED FOR ASSEMB	LY PURPOS	ES;			
	INDIVI ITEM	DUAL COMPONE	NTS MAY E	BE SHIPPED AS PARTS	WITHIN AN QTY.	INCLUDED KI	T. NOTE NO.]	
	1	MTC4164-020A-00		OSSMEMBER GALV	1	7.29 LBS	NOTE NO.	-	
	2	9674-1 GWF05A		5/8X3,STL,GALV WASHER HARDENED 5/8", 1.30	2 DD 4	0.08 LBS 0.04 LBS		-	
	4	GWL-05		OCK WASHER	2	0.03 LBS		-	
А	5				4	0.08 LBS		-	
	6 7	GB-03145 HKCLU02	3/8" X 1-1/2" BACKING P	GALV BOLT KIT	2	0.07 LBS 0.95 LBS		-	
	8				4	0.33 LBS			
	9	GN-03 3/8" GALV HEX NUT			4	0.02 LBS		1	
	10 11	10 GWL-03 3/8" GALV LOCK WASHER 11 GWF-03 3/8" GALV FLAT WASHER			4	0.01 LBS 0.01 LBS		-	
	12	MTC4164-LAB05		ANCHOR, CABLE LADDER	1	0.00 LBS		C 2025 Com	
			4						

C) 2025 CommScope, Inc. Confidential


4

	REVISIONS										
REV.		DESCRIPTION	DATE	APPROVED							
А		INITIAL RELEASE	RY1002 230CT23	EB1063 40181149CMO							
В	QTY FOF GWF05A NOTE FO	R 9674-1(ITEM 2) & GWL-05(ITEM 4) WAS 1EA, A(ITEM 3) & GN-05(ITEM 5) WAS 2EA; ADDED R EYEBOLT; CHG BOX FROM BX92 TO BXGB:	RY1002 19FEB24	EB1063 40188637CMO							
С		64-020A-00 WAS MTC4164-020-00; MTC4164- AS MTC4164-LAB01; CHG LOADING CAPACIT [\]	RY1002 (13MAY24	EB1063 40195296CMO							
D	MODIFIE	D THE FIELD INSTALLATION INSTRUCTIONS	RY1002 21JAN25	EB1063 40212493CMO							

D

С

В



A -PER EYEBOLT = 1000 LBS

B-IN ANY COMBINATION = 2000 LBS

-NOT TO BE USED FOR HOISTING -CABLE LADDER TO BE INSPECTED BY COMPETENT PERSON TO ENSURE PROPER INSTALLATION PRIOR TO INSTALL -DESIGNED TO BE UTILIZED ON "CL-0610-U" OR "CL-0620-U"

