


Base Product



Ultra Low Loss Singlemode MPO12 (Unpinned) to MPO12 (Unpinned)
Pre-terminated Trunk Cable, 1728-Fiber, 12-Fiber Rollable Ribbon Indoor
/Outdoor Central Tube, Low Smoke Zero Halogen/Riser

Product Classification

Regional Availability	Asia Australia/New Zealand Europe Latin America Middle East /Africa North America
Portfolio	CommScope®
Product Type	Fiber trunk cable assembly
Product Brand	SYSTIMAX ULL
Ordering Note	For additional jacket colors, please contact a CommScope Sales Representative For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

General Specifications


Color, boot A	Black
Color, connector A	Green
Color, boot B	Black
Color, connector B	Green
Construction Type	Rollable ribbon
Furcation Color	Yellow
Interface, Connector A	MPO-12/APC Female
Interface, Connector B	MPO-12/APC Female
Jacket Color	Black
Polarity	Method B Enhanced (ULL)
Fibers per Subunit, quantity	12
Total Fibers, quantity	1728

Dimensions

Breakout Length	33 in
Cable Assembly Length Range (m)	30 – 999
Cable Assembly Length Range (ft)	98 – 999

Cable Assembly Length Range (km)1.00 – 2.00

Ordering Tree



Mechanical Specifications

Cable Retention Strength, maximum11.24 lb @ 0 ° | 4.40 lb @ 90 °

Optical Specifications

Fiber ModeSinglemode

Fiber TypeG.657.A2, TeraSPEED®

Environmental Specifications

Operating Temperature-10 °C to +60 °C (+14 °F to +140 °F)

Environmental SpaceDual Rated LSZH/Riser

Packaging and Weights

Packaging TypeWood reel

Regulatory Compliance/Certifications

Agency	Classification
ANATEL	Compliant
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance

UJGMPMPSY

ROHS

UK-ROHS

Compliant

Compliant



Included Products

- 860638318
-
- MP012, ULTRA LOW LOSS, FEMALE, Singlemode, GREEN, 3mm